



Automatic film applicators **ZAA2600.HA**

Automatic Film Applicator for use with Heatable Plates




User experience

Multi-language menu guidance on the touch screen with storage of various application profile settings such as application length and drawing speed.




Reliability

Reproducible, operator-independent results allow for storage of various application profile settings such as application length and drawing speed.



Versatility

Thanks to its modular construction and compact design, it can be equipped with different kits for applications like scrub resistance, washability, crocking, and scratch resistance tests.



Instrument

Tech Specs

Display	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
Application length	Application length: up to $\approx$ 400 mm ($\approx$ 15.75")
Application width	Application width: up to 300 mm (11.81")
Weight	2600.HA: $\approx$ 24 kg ($\approx$ 52.9 lbs) glass plate only: 6.4 kg (14.1 lbs)
Battery	Power supply: 100 V - 240 V, 50 Hz - 60 Hz
Operating Temperature	Plates: heatable up to 150°C (302°F)
Temperature range	Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F)
Relative humidity	20% to 80%, no condensation
Drawing speed	1 - 500 mm/s (0.04 - 19.69"/s)
Resolution	Resolution: 1 mm/s (0.04"/s)

Standards & Guidelines	Description
ASTM D1640 (Depending on accessory)	
ASTM D4748-10	
ASTM D6279	
ASTM D823 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

Request a quote



Machine translated & automatically generated (English version prevails): 10.09.2025
Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

